

Russell Technologies India Pvt. Ltd. C – 2/290, Sec – F, Jankipuram, Lucknow -226021 U.P. India Telefax - +91 – 0522 - 4027541; Mobile: +91- 9450760411 www.russelltech-india.in; info@russelltech-india.com

Portable Hardness Tester Uee910



Functions & Features

- High quality and precision.
- Automatically identify 7 types of Impact devices for special application.
- Freely switch to hardness scales HRB, HRC, HV, HB, HS, HL.
- Direct calibration on HL,HRC,HB.
- PC Software for data transmission, analysis and measurement reports printing.
- Test at any angle, even upside down.
- Large LCD screen with back-light, showing all functions and parameters.
- Upper and lower limit and sound alarm.
- Conversion to tensile strength (U.T.S).
- 3 years warranty and life-long services.

Measuring Materials

• Steel and cast steel, alloy tool steel, stainless steel, gray cast iron, nodular cast iron, cast aluminum alloy, copper zinc alloys (brass), an alloy of copper and tin, copper (bronze), forged steel and other special metal materials.

Technical Parameters

Model	Uee910				
Measuring Range	(170-960)HLD,(17.9-69.5)HRC,(19-683)HB,(80-1042)HV,(30.6-102.6)HS, (59.1-88)HRA, (13.5-101.7)HRB				
Hardness parameter	HL, HRC,HRB, HS,HB,HV				
Accuracy	±6HLD				
Memory	600 groups				
PC Connection	Available				
Battery	2*AA				
Operating Temperature	-20 ℃ ~+60 ℃				
Dimensions	163×78×33mm				
Weight	240g				
Standard Configuration	Main unit, Impact Device type D, Calibration block,Small supporting ring, USB cable, Software, Backup accessories(Impact ball*1, Cable*1, Spanner *1), Cleaning brush,Operation manual,Certificate.				
Optional Accessories	Optional Impact Devices(D,DC,DL,D+15,G,C,E), Shaped support rings, Testing blocks				

Pictures





DataView						1 COLOR	1 100 3	
500 4	0.0	6.0 414.0	1					1110
400	٦.٢	7						1260
350-							88	188.8
300							88	000
250			····					0.0
200							88	0.00
150		1					88	888.81
102		-					8.8	8888
÷Ц.								1000
	1	2 3	4 5	6 7	5	9 10	0.0	0,0
								8 8 8 8 4 4
Ste	el	HL	D	Down	3	2017-6-30	88	0.0
	rerage		StdDev	Nettinun	<u> </u>	Minimum		
4	23.3		8.3	430.0		414.0	0.00	3 0 0 0 3
					2			

